

# Dispensing Tips

DYMAX provides a range of both needle and taper dispense tips in various lengths, gauges and shapes to meet your specific application. Tip selection is critical when precision is required and the length, shape and size of the tip used will define the shape of the fluid deposit and the performance of your dispense system. For assistance in optimal tip selection, contact the DYMAX Application Engineering team.

## Free-Flow Taper Tips (sold in packages of 50)

Free-flow taper tips are molded from polyethylene with a UV-light block additive, making them compatible with a wide variety of medium-to-high viscosity fluids including UV light-curable materials.

Gauge		Color	Part Number by Length		ID	
			1.25" [31.75 mm]		mm	in
●	14	White		T14-125-TT-50	1.60	0.063
●	16	Charcoal		T16-125-TT-50	1.19	0.047
●	18	Green		T18-125-TT-50	0.84	0.033
●	20	Pink		T20-125-TT-50	0.58	0.023
●	22	Blue		T22-125-TT-50	0.41	0.016
●	25	Red		T25-125-TT-50	0.25	0.010



## Stainless Steel Dispensing Tips (sold in packages of 50)

The most versatile of all tips, these dispensing tips are comprised of a polypropylene hub and passivated 304 stainless steel tubing. Stainless steel dispensing tips can be used with a wide variety of low-to-high viscosity fluids including adhesives, epoxies, greases, oils, paints, solder masks, solvents, and more.

Gauge		Color	Part Number by Length		ID		
			0.5" [12.7 mm]	1" [25.4 mm]	mm	In	
●	14	White		T14-050-50	T14-100-50	1.60	0.063
●	15	Amber		T15-050-50	T15-100-50	1.32	0.052
●	16	Charcoal		T16-050-50	T16-100-50	1.19	0.047
●	18	Green		T18-050-50	T18-100-50	0.84	0.033
●	20	Pink		T20-050-50	T20-100-50	0.58	0.023
●	21	Purple		T21-050-50	T21-100-50	0.51	0.020
●	23	Orange		T23-050-50	T23-100-50	0.33	0.013
●	25	Red		T25-050-50	T25-100-50	0.25	0.010
●	27	Gray		T27-050-50	T27-100-50	0.20	0.008
●	30	Lavender		T30-050-50		0.15	0.006



## PTFE-Lined Dispensing Tips (sold in packages of 50)

PTFE-lined needle tips are ideal for dispensing low-viscosity fluids. They resist clogging, making them great for use with gel cyanoacrylates. PTFE-lined dispensing tips can also be used with anaerobics, solvents, epoxies, grease, oils, pastes, and more.

Size	Color	Part Numbers by Length		ID	
		0.5" [12.7 mm]		mm	In
●	Gray	T020-050-TL-50		0.51	0.020
.	Pink	T006-050-TL-50		0.15	0.006



## Polypropylene Flexible Dispensing Tips (sold in packages of 50)

Polypropylene dispensing tips are ideal for difficult-to-reach applications. These soft, flexible tips prevent scratching of the part when the needle comes in contact with the work surface.

Gauge	Color	Part Numbers by Length		ID	
		0.5" [12.7 mm]		mm	In
●	15	Amber	T15-050-PP-50	1.32	0.052
●	18	Green	T18-050-PP-50	0.84	0.033
●	20	Pink	T20-050- PP-50	0.58	0.023
●	25	Red	T25-050- PP-50	0.25	0.010



© 2011 DYMAX Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by DYMAX Corporation, U.S.A. The data contained in this bulletin is of a general nature and is based on laboratory test conditions. DYMAX Europe GmbH does not warrant the data contained in this bulletin. Any warranty applicable to products, its application and use is strictly limited to that contained in DYMAX Europe GmbH's General Terms and Conditions of Sale published on our homepage [http://www.dymax.com/de/pdf/dymax\\_europe\\_general\\_terms\\_and\\_conditions\\_of\\_sale.pdf](http://www.dymax.com/de/pdf/dymax_europe_general_terms_and_conditions_of_sale.pdf). DYMAX Europe GmbH does not assume any responsibility for test or performance results obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by someone other than DYMAX Corporation or act as a grant of license under any DYMAX Corporation Patent. DYMAX Europe GmbH recommends that each user adequately test its proposed use and application of the products before actual repetitive use, using the data contained in this bulletin as a general guide. PB009EU 11/28/2011

DYMAX Corporation  
860.482.1010  
info@dymax.com  
[www.dymax.com](http://www.dymax.com)

DYMAX Europe GmbH  
+49 (0) 611.962.7900  
info\_de@dymax.com  
[www.dymax.de](http://www.dymax.de)

DYMAX UV Adhesives &  
Equipment (Shenzhen) Co Ltd  
+86.755.83485759  
dymaxasia@dymax.com  
[www.dymax.com.cn](http://www.dymax.com.cn)

DYMAX Asia  
(Hong Kong) Ltd  
+852.2460.7038  
dymaxasia@dymax.com  
[www.dymax.com.cn](http://www.dymax.com.cn)

DYMAX Korea LLC  
82.2.784.3434  
info@dymax.kr  
[www.dymax.co.kr](http://www.dymax.co.kr)

