

- Comprised of aluminum making them safe for use with many fluids including light-curable materials
- Materials are housed in the cartridge inside the reservoir retainer preventing fluid contamination
- Reservoir design allows for quick and easy product chageover with no maintenance or cleaning required
- · Airtight cover seal eliminates leak points
- Available in 5 different sizes making them compatible with most common adhesive cartridge sizes
- Compatible with Dymax lab stands for stable mounting with a small footprint

## **Cartridge Drop-In Reservoirs**

Dymax offers a complete line of cartridge drop-in reservoirs for use with fluid dispensing systems. Five sizes, ranging from 2.5 oz [74 mL] to 32 oz [900 mL], are available making these reservoirs compatible with common polyethylene cartridge sizes. The material reservoirs are made of lightweight aluminum and are designed so that they can be securely attached to a Dymax lab stand. The retainer's cover features a silicone O-ring which provides an air-tight seal, eliminating leak points. To use the material reservoir, operators simply load a prefilled cartridge into the cartridge retainer, install the reservoir cap, and apply air. Materials are housed inside the cartridge and never come in contact with the outer aluminum retainer, eliminating the need for maintenance or cleaning and preventing any contamination of the fluid while inside the material reservoir. This feature also facilitates quicker, easier product changeover.

Standard cartridge drop-in reservoir packages include a cartridge retainer, retainer cap, adjustment knobs, and a quick disconnect.





T15257







20 oz (550 mL)

T15223



32 oz (900 mL) T15224

2.5 oz (74 mL) T15254

6 oz (160 mL)

12 oz (300 mL) T14085

Specifications	
Part Number/Size	T15254Cartridge Drop-In Reservoir, 2.5 oz [74 mL]T15257Cartridge Drop-In Reservoir, 6 oz [160 mL]T14085Cartridge Drop-In Reservoir, 12 oz [300 mL]T15223Cartridge Drop-In Reservoir, 20 oz [550 mL]T15224Cartridge Drop-In Reservoir, 32 oz [900 mL]
Package Includes	Cartridge Retainer, Retainer Cap, Adjustment Knobs, & Quick Disconnect
Material	Aluminum (Body) & Silicone (0-Ring)
Air Inlet	1/8 in [0.32 cm] Fitting
Unit Warranty	One year
Accessories	T15279 Lab Stand, 24 in [60.96 cm]
Recommended Spare Parts	T16869Silicone O-Ring for the 6 & 12 oz ReservoirT16870Silicone O-Ring for the 20 & 32 oz ReservoirT16789Reservoir Air-Line Kit, 11 ft [3.35 M]



Silicone O-Ring (Installed in Reservoir Cap)



24 in [60.96 cm] Lab Stand



Reservoir Air-Line Kit



.....

Americas USA | +1.860.482.1010 | info@dymax.com

Europe Germany | +49 611.962.7900 | info\_de@dymax.com Ireland | +353 21.237.3016 | info\_ie@dymax.com

## Asia

Singapore | +65.67522887 | info\_ap@dymax.com Shanghai | +86.21.37285759 | dymaxasia@dymax.com Shenzhen | +86.755.83485759 | dymaxasia@dymax.com Hong Kong | +852.2460.7038 | dymaxasia@dymax.com Korea | +82.31.608.3434 | info\_kr@dymax.com

©2020 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by, Dymax Corporation, U.S.A.

Technical data provided is of a general nature and is based on laboratory test conditions. Dymax does not warrant the data contained in this bulletin. Any warranty applicable to the product, its application and use, is strictly limited to that contained in Dymax's standard Conditions of Sale. Dymax does not assume responsibility for test or performance results obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by some or other than Dymax or act as a grant of license under any Dymax Corporation Patent. Dymax recommends that each user adequately test its proposed use and application before actual repetitive use, using the data contained in this bulletin as a general guide. **PB032DA** 10/20/2016